














ROOSTEVABA TERASPUNUTISEGA SURVEVOOLIKUD VEELE
PARINOX 257 norm EN 13618



GARANTII
10
AASTAT

 EPDM mm	 INOX AISI 304 Ø mm	 CW 614N	 INOX Ø mm 14	 R = mm	 bar	 °C	 mm	 lt/min - 3 bar
DN8 - 8	12		Ø mm 14	30	10	-5 +90	6,2	32

	PIKKUS	KOOD	HIND	HIND+20%
F1/2"-F1/2" 	200 mm	60002	2,53	3,03
	300 mm	60003	2,80	3,36
	400 mm	60004	3,10	3,72
	500 mm	60005	3,37	4,04
	600mm	60006	3,58	4,30
	800 mm	60008	4,28	5,13
	1000 mm	60010	4,68	5,62
	1250 mm *	60012	4,04	4,85
	1500 mm	60015	6,08	7,30
	2000 mm	60020	7,74	9,29
F1/2"-M1/2" 	200 mm	60102	2,80	3,36
	300 mm	60103	3,06	3,67
	400 mm	60104	3,37	4,04
	500 mm	60105	3,59	4,31
	600 mm	60106	3,82	4,58
	800 mm	60108	4,50	5,40
	1000 mm	60110	4,95	5,94
	1250 mm *	60112	4,25	5,10
F1/2"-MDB10 	200 mm	60302	2,980	3,57
	300 mm	60303	3,150	3,78
	400 mm	60304	3,540	4,25
	500 mm	60305	3,730	4,47
	600 mm	60306	3,950	4,74
	M1/2"-MDB10 	200 mm	60402	3,200
300 mm		60403	3,470	4,16
400 mm		60404	3,770	4,52
500 mm		60405	3,980	4,78
600 mm		60406	4,220	5,06

* lõpumüük

